

# PIN Power Inductor RCH-110



Halogen Free



### Description

- Ferrite drum core construction.
- Magnetically unshielded.
- L × W × H: 10.5 × 10.5 × 10.5mm Max.
- Product weight: 3.1g(Ref.)
- Moisture Sensitivity Level: 1
- RoHS compliance.
- Halogen Free available.

### Environmental Data

- Operating temperature range: -40°C ~ +100°C (including coil's self temperature rise)
- Storage temperature range: -40°C ~ +100°C


### Packaging

- Box packaging.


### Applications

- Ideally used in Printers, LCD TV, DVD, Copy Machine, Mainboard of the compounding machines etc. as DC-DC Converter inductors.

### Dimension - [mm]



### Schematics - [mm]



# PIN Power Inductor RCH-110



## Electrical Characteristics

PART NO.	STAMP	INDUCTANCE [WITHIN] ※1	D.C.R. ( $\Omega$ ) [MAX.] (at20°C)	RATED CURRENT (A)※2	S.R.F. (MHz) TYP.
RCH110NP-100M	100M	10 $\mu$ H $\pm$ 20%	0.022	5.3	14
RCH110NP-120M	120M	12 $\mu$ H $\pm$ 20%	0.023	4.9	11
RCH110NP-150M	150M	15 $\mu$ H $\pm$ 20%	0.026	4.4	7.7
RCH110NP-180M	180M	18 $\mu$ H $\pm$ 20%	0.033	4.0	7.1
RCH110NP-220M	220M	22 $\mu$ H $\pm$ 20%	0.037	3.6	6.8
RCH110NP-270M	270M	27 $\mu$ H $\pm$ 20%	0.048	3.3	6.1
RCH110NP-330K	330K	33 $\mu$ H $\pm$ 10%	0.055	2.9	6.0
RCH110NP-390K	390K	39 $\mu$ H $\pm$ 10%	0.073	2.7	8.6
RCH110NP-470K	470K	47 $\mu$ H $\pm$ 10%	0.083	2.5	8.1
RCH110NP-560K	560K	56 $\mu$ H $\pm$ 10%	0.092	2.3	7.6
RCH110NP-680K	680K	68 $\mu$ H $\pm$ 10%	0.12	2.1	6.3
RCH110NP-820K	820K	82 $\mu$ H $\pm$ 10%	0.14	1.9	6.0
RCH110NP-101K	101K	100 $\mu$ H $\pm$ 10%	0.16	1.7	5.7
RCH110NP-121K	121K	120 $\mu$ H $\pm$ 10%	0.20	1.5	4.8
RCH110NP-151K	151K	150 $\mu$ H $\pm$ 10%	0.23	1.4	4.2
RCH110NP-181K	181K	180 $\mu$ H $\pm$ 10%	0.31	1.3	3.9
RCH110NP-221K	221K	220 $\mu$ H $\pm$ 10%	0.34	1.1	3.8
RCH110NP-271K	271K	270 $\mu$ H $\pm$ 10%	0.40	1.0	3.4
RCH110NP-331K	331K	330 $\mu$ H $\pm$ 10%	0.52	0.93	2.8
RCH110NP-391K	391K	390 $\mu$ H $\pm$ 10%	0.65	0.86	2.7
RCH110NP-471K	471K	470 $\mu$ H $\pm$ 10%	0.71	0.78	2.5
RCH110NP-561K	561K	560 $\mu$ H $\pm$ 10%	1.0	0.71	2.2
RCH110NP-681K	681K	680 $\mu$ H $\pm$ 10%	1.1	0.65	2.1
RCH110NP-821K	821K	820 $\mu$ H $\pm$ 10%	1.3	0.59	2.0
RCH110NP-102K	102K	1.0 mH $\pm$ 10%	1.7	0.53	1.7

※1. Inductance measuring condition : at 1.0kHz













※2. This indicates the value of current when the inductance 10% lower than its initial value or D.C current when  $\Delta T=40^{\circ}\text{C}$ , whichever is lower ( $T_a=20^{\circ}\text{C}$ ).

# PIN Power Inductor RCH-110



## Saturation Current & Temperature Rise Graph

— L (20°C) — L (100°C) —  $\Delta T$















# PIN Power Inductor RCH-110



## Saturation Current & Temperature Rise Graph

— L (20°C) — L (100°C) —  $\Delta T$




# PIN Power Inductor RCH-110



## Saturation Current & Temperature Rise Graph

— L (20°C) — L (100°C) —  $\Delta T$



Please refer to the sales offices on our website - <http://www.sumida.com>

### Hong Kong

Tel.+852-2880-6781  
FAX.+852-2565-9600  
[sales@hk.sumida.com](mailto:sales@hk.sumida.com)

### Saitama(Japan)

Tel.+81-48-691-7300  
FAX.+81-48-691-7340  
[sales@jp.sumida.com](mailto:sales@jp.sumida.com)

### Chicago

Tel.+1-847-545-6700  
FAX. +1-847-545-6720  
[sales@us.sumida.com](mailto:sales@us.sumida.com)

### Shanghai

Tel.+86-21-5836-3299  
FAX.+86-21-5836-3266  
[shanghai.sales@cn.sumida.com](mailto:shanghai.sales@cn.sumida.com)

### Seoul

Tel.+82-2-6237-0777  
FAX.+82-2-6237-0778  
[sales@kr.sumida.com](mailto:sales@kr.sumida.com)

### Oberzell

Tel.+49-8591-937-0  
FAX. +49-8591-937-103  
[contact@eu.sumida.com](mailto:contact@eu.sumida.com)

### Shenzhen

Tel.+86-755-8291-0228  
FAX.+86-755-8291-0338  
[shenzhen.sales@cn.sumida.com](mailto:shenzhen.sales@cn.sumida.com)

### Singapore

Tel.+65-6296-3388  
FAX.+65-6841-4426  
[sales@sg.sumida.com](mailto:sales@sg.sumida.com)

### Neumarkt

Tel.+49-9181-4509-110  
FAX. +49-9181-4509-310  
[infocomp@eu.sumida.com](mailto:infocomp@eu.sumida.com)

### Taipei

Tel.+886-2-8751-2737  
FAX.+886-2-8751-2738  
[sales@tw.sumida.com](mailto:sales@tw.sumida.com)

### San Jose

Tel.+1-408-321-9660  
FAX.+1-408-321-9308  
[sales@us.sumida.com](mailto:sales@us.sumida.com)